

農業機械用タイヤ諸元一覧表

※適用リム/リムは車両メーカー採用の主要リムを記載しています。

・印サイズはこの表記のバタンとなります。

▶トラクター用

バタン	タイヤサイズ	プライ	構造		適用リム	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ
			W/T	T/L				
T13H	7-14	2	●		5-JA	697	162	TR413
	7-16	4	●		5-JA	748	165	TR413
	8-16	4	●		5-JA	798	192	TR413
	8-18	4	●		W-7	848	204	TR413
	8-18	4	●		W-7	848	206	TR15,TR218A
	83-20	4	●		W-7	893	206	TR15,TR218A
	95-20	4	●		W-8	949	240	TR15,TR218A
	83-22	4	●		W-7	945	212	TR15,TR218A
	95-22	4	●		W-8	995	240	TR15,TR218A
	83-24	4	●		W-7	995	211	TR15,TR218A
	95-24	4	●		W-8	1050	240	TR15,TR218A
	112-24	4	●		W-10	1095	281	TR15,TR218A
	・T13HA 124-24	4	●		W-11	1160	310	TR15,TR218A
	124-24	4	●		W-11	1160	310	TR15,TR218A
	136-24	4	●		W-12	1210	345	TR15,TR218A
	・T11H 83-26	4	●		W-7	1045	204	TR15
	112-26	4	●		W-10	1155	279	TR15
	124-26	4	●		W-11	1210	310	TR15,TR218A
	136-26	4	●		W-12	1260	340	TR15,TR218A
	136-28	4	●		W-12	1310	340	TR15,TR218A
124-32	4	●		W-11	1360	317	TR15,TR218A	
T10H	112-24	4	●		W-10	1095	281	TR15,TR218A
	124-24	4	●		W-11	1160	324	TR15,TR218A
	136-24	4	●		W-12	1210	345	TR15,TR218A
	95-26	4	●		W-8	1100	236	TR15
	112-26	4	●		W-10	1155	279	TR15
	124-26	4	●		W-11	1210	310	TR15,TR218A
	136-26	4	●		W-12	1260	340	TR15,TR218A
	112-28	4	●		W-10	1205	279	TR15,TR218A
	124-28	4	●		W-11	1260	317	TR15,TR218A
	136-28	4	●		W-12	1310	340	TR15,TR218A
136-28	6	●		W-12	1310	340	TR15,TR218A	
FSLSC	・FSLSD 112-24	4	●		W-10	1095	280	TR15,TR218A
	124-24	4	●		W-11	1150	314	TR15,TR218A
	136-24	4	●		W-12	1210	345	TR15,TR218A
	・FSL 124-26	4	●		W-11	1244	322	TR15,TR218A
	124-26	4	●		W-11	1210	315	TR15,TR218A
	136-26	4	●		W-12	1260	345	TR15,TR218A
	124-28	4	●		W-11	1262	314	TR15,TR218A
	136-28	6	●		W-12	1310	345	TR15,TR218A
	・FSL 149-28	6	●		W-13	1406	380	TR218A
	169-30	6	●		W-15L	1512	429	TR218A
	124-32	4	●		W-11	1358	315	TR218A
	124-32	6	●		W-11	1358	315	TR218A
	124-36	6	●		W-11	1465	319	TR218A
	136-38	6	●		W-12	1578	348	TR218A
FLOO	7-16	6	●		5-JA	740	173	TR15,TR218A
	8-16	4	●		5-JA	790	193	TR15,TR218A
	95-16	6	●		W-8	845	243	TR15,TR218A
	95-18	4	●		W-8	895	243	TR15,TR218A
	95-18	6	●		W-8	895	243	TR15,TR218A
	83-20	6	●		W-7	890	211	TR15,TR218A
	95-20	6	●		W-8	945	243	TR15,TR218A
	112-20	6	●		W-10	1003	284	TR218A
	83-22	6	●		W-7	945	210	TR15,TR218A
	95-22	4	●		W-8	995	243	TR15,TR218A
	95-22	6	●		W-8	995	243	TR15,TR218A
	83-24	6	●		W-7	993	205	TR15,TR218A
	95-24	6	●		W-8	1050	243	TR15,TR218A
	112-24	6	●		W-10	1088	275	TR15,TR218A
	124-24	4	●		W-11	1150	320	TR15,TR218A
	124-24	6	●		W-11	1150	320	TR15,TR218A
	136-24	4	●		W-12	1210	345	TR15,TR218A
	136-24	6	●		W-12	1210	345	TR15,TR218A
	149-24	4	●		W-13	1247	383	TR15,TR218A
	149-24	6	●		W-13	1247	383	TR15,TR218A
	136-26	4	●		W-12	1260	355	TR15,TR218A
	124-28	6	●		W-11	1260	320	TR15,TR218A
	136-28	4	●		W-12	1310	345	TR15,TR218A
	136-28	6	●		W-12	1310	345	TR15,TR218A
	149-28	6	●		W-13	1365	380	TR218A
	169-28	6	●		W-15L	1400	442	TR218A

バタン	タイヤサイズ	プライ	構造		適用リム	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ	
			W/T	T/L					
FLOO	169-30	6	●		W-15L	1485	442	TR218A	
	184-30	6	●		W-16L	1547	487	TR218A	
	124-32	6	●		W-11	1360	320	TR218A	
	169-34	6	●		W-15L	1587	440	TR218A	
	184-34	6	●		W-16L	1635	478	TR218A	
	184-34	8	●		W-16L	1635	478	TR218A	
	139-36	6	●		W-12	1478	343	TR218A	
	155-38	6	●		W-14L	1582	394	TR218A	
	169-38	8	●		W-15L	1671	442	TR218A	
	184-38	8	●		W-16L	1727	480	TR218A	
	FSL	112-28	4	●		W-10	1206	287	TR15,TR218A
		112-28	6	●		W-10	1206	287	TR15,TR218A
		124-28	4	●		W-11	1262	320	TR15,TR218A
		124-28	6	●		W-11	1262	320	TR15,TR218A
149-28		6	●		W-13	1370	387	TR218A	
169-30		6	●		W-15L	1485	436	TR218A	
184-30		6	●		W-16L	1547	457	TR218A	
124-32		6	●		W-11	1364	320	TR218A	
124-36		6	●		W-11	1465	320	TR218A	
136-38		6	●		W-12	1574	345	TR218A	
FSLF	7-16	4	●		5-JA	740	170	TR15,TR218A	
	7-16	4	●		6.00F	740	180	TR15,TR218A	
	8-16	4	●		5-JA	790	193	TR15,TR218A	
	95-16	4	●		W-8	845	248	TR15,TR218A	
	124-16	4	●		W-11	955	322	TR218A	
	112-24	4	●		W-10	1088	274	TR15,TR218A	
	112-24	6	●		W-10	1088	274	TR15,TR218A	
5-26	4	●		4-JA	900	122	TR15A		
FSLH	8-18	4	●		W-7	840	207	TR15,TR218A	
	124-24	6	●		W-11	1150	317	TR15,TR218A	
	149-24	6	●		W-13	1247	386	TR218A	
	169-34	6	●		W-15L	1587	440	TR218A	
	184-34	6	●		W-16L	1635	470	TR218A	
149-38	6	●		W-13	1618	390	TR218A		
FH80	184-34	6	●		W-16L	1635	467	TR218A	
FSLM	450-10	4	●		3.00D	510	120	TR13	
	6-10	4	●		5-JA	550	155	TR13	
	5-12	2	●		4-JA	550	123	TR13	
	5-12	4	●		4-JA	550	123	TR13	
	500-12	2	●		3.00D	581	131	TR13	
	500-12	4	●		3.00D	581	131	TR13	
	6-12	4	●		5-JA	600	155	TR13	
	600-12	4	●		4.00E	636	162	TR13	
	600-12	6	●		4.00E	638	163	TR13	
	5-14	4	●		4-JA	605	128	TR13	
	6-14	2	●		5-JA	653	155	TR13	
	6-14	4	●		5-JA	653	158	TR13	
	7-14	4	●		5-JA	690	170	TR13	
	7-16	4	●		5-JA	740	170	TR15,TR218A	
	8-16	4	●		5-JA	789	197	TR15,TR218A	
	400-18	4	●		2.75D	690	108	TR15	
	8-18	4	●		W-7	840	207	TR15,TR218A	
8-18	6	●		W-7	840	207	TR15,TR218A		
72-20	4	●		W-6	845	179	TR15		
83-20	4	●		W-7	890	209	TR15,TR218A		
83-20	6	●		W-7	890	209	TR15,TR218A		
95-22	6	●		W-8	996	242	TR15,TR218A		
95-24	6	●		W-8	1047	242	TR15,TR218A		
FSR	400-9	2	●		3.00D	458	114	TR13	
	450-10	4	●		3.00D	488	120	TR13	
	500-10	4	●		3.00D	530	132	TR13	
	400-12	4	●		3.00D	538	113	TR13	
	400-15	4	●		3.00D	613	113	TR15	
	500-15	4	●		3.00D	660	133	TR15	
	600-16	4	●		4.00E	737	167	TR15	
	650-16	6	●		4.50E	763	180	TR15	
	750-16	6	●		5.50F	815	210	TR15	
	600-19	6	●		4.00E	818	164	TR15	
	FSLW	72-20	4	●		W-6	845	179	TR15
112-24		4	●		W-10	1088	280	TR15,TR218A	
112-24		6	●		W-10	1088	285	TR15,TR218A	
FSM	750-16	6	●		5.50F	808	211	TR15	

農業機械用タイヤ諸元一覧表

▶ 耕うん機用

ボタン	タイヤサイズ	プライ	構造		適用リム	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ
			W/T	T/L				
U10L	5-12	2	●	●	4-JA	545	126	TR13(W/T),TR413(T/L)
	500-12	2	●	●	3.00D	573	131	TR13(W/T),TR413(T/L)
	6-12	2	●	●	5-JA	600	158	TR413
	600-12	2	●	●	4-JA	629	154	TR13(W/T),TR413(T/L)
AR○○	350-5	2	●	●	3.00SP	308	93	TR87(W/T),TR413(T/L)
	400-7	2	●		3.00D	400	111	TR13
	400-8	2	●		3.00D	445	111	TR13
	400-10	2	●		3.00D	492	111	TR13
	450-10	2	●		3.00D	515	120	TR13
	400-12	2	●		3.00D	540	110	TR13
	5-12	2	●		4-JA	550	125	TR13
	500-12	2	●		3.00D	581	133	TR13
	6-12	2	●		5-JA	600	158	TR13
	600-12	2	●		4.00E	636	157	TR13
	600-12	4	●		4.00E	636	160	TR13
	5-14	4	●		4-JA	605	128	TR15
	6-14	4	●		5-JA	653	155	TR13
	AL○○	400-16	2	●		3.00D	650	108
440-21		2	●		2.75D	800	120	TR13
440-21		4	●		2.75D	800	120	TR13
130/90-21AG		-	●		2.75D	800	120	TR13
TA	350-5	2	●		3.00SP	300	100	JS87
	140/60D5	2		●	4.50SP	300	140	TR413
	350-6	2	●	●	3.00SP	320	93	TR13(W/T),TR413(T/L)
	100/85D6	2		●	3.00	330	100	TR413
	350-7	2	●	●	3.00D	347	98	TR13(W/T),TR413(T/L)
	400-7	2	●	●	3.00D	400	111	TR13(W/T),TR413(T/L)
	400-8	2	●	●	3.00D	435	111	TR13(W/T),TR413(T/L)
	400-9	2	●	●	3.00D	458	111	TR13(W/T),TR413(T/L)
	400-10	2	●	●	3.00D	483	111	TR13(W/T),TR413(T/L)
	450-10	2	●		3.00D	510	123	TR13
	400-12	2	●	●	3.00D	540	111	TR13(W/T),TR413(T/L)
	5-12	2	●		4-JA	550	125	TR13
	500-12	2	●	●	3.00D	581	133	TR13(W/T),TR413(T/L)
	6-12	2	●	●	5-JA	600	158	TR13(W/T),TR413(T/L)
600-12	2	●	●	4.00E	636	157	TR13(W/T),TR413(T/L)	
6-14	2	●		5-JA	657	162	TR13	
TA10	400-12	2		●	3.00D	525	111	TR413
A10L	300-12	4	●		1.85	457	70	TR4S

▶ インPLEMENT用

ボタン	タイヤサイズ	プライ	構造		適用リム	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ
			W/T	T/L				
FI 2	100/80-12	4		●	7-JA	695	244	TR413
	100/80-12	6		●	7-JA	695	244	TR413
	115/80-15	10		●	10-JJ	842	332	TR413
FI 3	900-15	8	●		6-LB	850	252	TR15
AL	900-13	6	●		5-1/2K	792	254	TR15

▶ 田植機用

・印サイズはこの表記のボタンとなります。

ボタン	タイヤサイズ	プライ	構造		適用リム	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ
			W/T	T/L				
AT○○	300-16	4	●		1.85	620	76	TR4
	250-17	4	●		1.60A	604	60	TR4
	275-17	4	●		1.85	600	70	TR4S
	300-17	4	●		1.85	650	76	TR4S
	250-18	4	●		1.60A	625	60	TR4S
	300-23	4	●		MT1.85	765	80	TR4S
	300-25	4	●		SP1.85	815	76	TR4S
	300-26	4	●		MT1.85	865	80	TR4S
	300-28	4	●		MT1.85	900	80	TR4S
	R13LA	76×12/6-23	4	●		1.70	764	60
81×18/6-25		4	●		1.70	810	60	TR4S
87×18/6-27		4	●		1.70	865	64	TR4S
92×18/6-29		4	●		1.70	915	60	TR4S
・R13LB 60/100-25AG		-	●		1.70	810	60	TR4S
60/100-31AG		-	●		1.70	970	60	TR4S
R12L	62×12/A-15	4	●		MT2.75	624	108	TR4
	56×6/6-16	4	●		1.40	556	55	TR4S
R14L	60/90-25AG	-	●		1.70	795	63	TR4S
	60/90-27AG	-	●		1.70	850	63	TR4S
R16L	120/90-26AG	-	●		4-JA	940	125	TR15

▶ 収穫機(バインダー)用

・印サイズはこの表記のボタンとなります。

ボタン	タイヤサイズ	プライ	構造		適用リム	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ
			W/T	T/L				
PL	16×700-8	2	●	●	5.50	403	180	TR13(W/T),TR413(T/L)
	16×700-8	4	●		5.50	403	180	TR413
	17×700-8	2		●	5.50	435	185	TR413
	18×700-8	2		●	5.50	435	185	TR413
	19×800-8	2		●	7.00	480	210	TR413
	19×1000-8	2		●	8.50	480	260	TR413
PL3	16×1000-8	2		●	8.50	410	255	TR413
PF	17×70-8	-		●	5.50	430	170	TR413
	18×70-8	-		●	6.50	455	175	TR413
	19×700-8	-		●	6.50	480	180	TR413
PFH	18×70-8	-		●	5.50	427	180	TR413
	・PFHB18×90-8	-		●	7.50	440	233	TR413
	・PFHB18×120-8	-		●	10.50	440	305	TR413
B10L	18×80-8	-		●	6.50	420	200	TR413
	18×100-8	-		●	5.50	420	235	TR413
	19×110-8	-		●	9.00	460	270	TR413
FTI	18×70-8	-		●	3.00	460	175	TR413
	18×100-8	-		●	5.50	445	250	TR413
	19×90-8	-		●	4.50	464	225	TR413
	20×80-10	-		●	4.00	485	205	TR413

※適用リム／リムは車両メーカー採用の主要リムを記載しています。

▶ 草芝刈機・ゴルフカート用

パタン	タイヤサイズ	プライ	構造		適用リム	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ	
			W/T	T/L					
SO	18×950- 8	2	●		7.00I	433	223	TR413	
PD	13×600- 8	2	●		5.00	342	148	TR413	
	18×700- 8	2	●		5.50	457	170	TR413	
	18×700- 8	4	●		5.50	457	170	TR413	
	18×700- 8	6	●		5.50	460	177	TR413	
	18×850- 8	4	●		7.00I	448	213	TR413	
	18×950- 8	4	●		7.00	460	230	TR413	
	19×800-10	2	●		7.00D	490	210	JS2	
	19×800-10	4	●		7.00D	490	217	TR413	
	20×800-10	4	●		5.00D	495	173	JS2	
	20×800-10	4	●		7.00I	495	203	TR413	
	23×850-12	4	●		7.00I	578	213	TR413	
	27×850-15	4	●		7.00I	681	214	TR15	
	PD5	13×500-6	2	●		3.50A	320	122	TR413
		16×650-8	2	●		5.375I	406	165	TR413
		16×650-8	6	●		5.375I	415	168	TR413
PD1	16×650-8	2	●		5.375I	406	165	TR413	
	16×650-8	4	●		5.375I	411	165	TR413	
	16×450-9	2	●		3.00D	401	104	TR13	
	205×800-10	4	●		6.00I	526	208	TR413	
	22×850-12	4	●		7-JA	546	216	TR413	
	23×1050-12	4	●		8-1/2JA	582	264	TR413	
	24×850-12	4	●		7-JA	602	216	TR413	
	26×1200-12	4	●		10LB	660	303	TR413	
	24×850-14	4	●		7-JA	602	216	TR413	
	25×850-14	4	●		7-JA	639	219	TR413	
	27×850-15	4	●		7-JA	681	214	TR413	
	29×1200-15	4	●		10-LB	757	297	TR413	
	31×135-15	4	●		10-LB	777	348	TR413	
	31×155-15	4	●		13-LB	785	397	TR413	
	136-16	4	●		W-12	988	357	TR218A	
	355/80D20	4	●		W-11	1076	345	TR218A	
	475/65D20	4	●		W-15L	1126	465	TR413	
	PD2	21×1100-10	2	●	●	8.50I	528	274	TR13(W/T),TR413(T/L)
	PD3	14×500-6	2	●		3.50A	350	130	TR413
18×850-8		2	●		7.00	448	213	TR413	
M40B	16×650-8	2	●		5.375I	406	165	TR413	
	16×650-8	4	●		5.375I	406	169	TR413	
	20×1000-8	2	●		8.5-JA	500	254	TR413	
	20×1000-8	4	●		8.5-JA	500	265	TR413	
	20×800-10	4	●		6.00I	495	193	TR413	
	23×850-12	4	●		7-JA	578	216	TR413	
	23×1050-12	2	●		8.5-JA	582	264	TR413	
	23×1050-12	4	●		8.5-JA	582	264	TR413	
	24×850-12	4	●		7-JA	614	224	TR413	
	315/75D15	4	●		10-LB	853	316	TR413	
	315/80D16	6	●		10-LB	910	316	TR413	
M50G	31×135-15	6	●		10-LB	777	340	TR413	
FD	6-12	4	●		5-JA	564	155	TR13	
	6-14	4	●		5-JA	614	155	TR13	
	7-14	4	●		5-JA	660	175	TR13	
	8-16	4	●		6.00F	805	220	TR15	
	112-24	4	●		W-10	1071	285	TR15,TR218A	
	136-28	6	●		W-12	1287	355	TR218A	
PR	11×400-5	2	●		3.00	272	97	TR413	
	14×500-6	2	●		3.50A	350	125	TR413	
	18×850-8	4	●		7.00I	445	213	TR413	

▶ 農用運搬車・不整地走行車用

パタン	タイヤサイズ	プライ	構造		適用リム	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ
			W/T	T/L				
FG	19×750-8	2	●		5.50E	480	177	TR13
	19×1000-8	2	●		8.50	485	255	TR13
FM1	17×800-8	4	●	●	7.00	440	208	TR413
FM2	17×800-8	4	●		7.00	448	205	TR413
	26×1400-12	6	●		12.00I	660	332	TR15
FM3	23×900-12	4	●		7-JA	581	215	TR13
K10H	26×1000-12	8	●		8.5-JA	660	260	TR13

荷車用タイヤ諸元一覧表

※適用リム／リムは車両メーカー採用の主要リムを記載しています。

▶ 農用運搬車・不整地走行車用

・印サイズはこの表記のパタンとなります。

パタン	タイヤサイズ	プライ	構造		適用リム	タイヤ外径 (m/m)	タイヤ断面幅 (m/m)	バルブ
			W/T	T/L				
UL	250-4	4	●		1.75	225	63	TR87S
	275-4	2	●		1.75	234	70	TR87S
	300-4	4	●		2.10(1.75)	256	82(78)	TR87S
	350-5	2	●		3.00SP	289	92	TR87S
	350-5	4	●		3.00SP	290	94	TR87S
	・PD3 400-5	2	●		3.00SP	320	105	TR87S,TR244
	400-5	4	●		3.00SP	310	102	TR87S,TR244
	325-8	2	●		1.75	366	84	JS87
	400-8	4	●		3.00D	410	111	JS244A,TR13
	400-8	6	●		3.00D	410	111	JS244A,TR13
	・ULS 500-8	4	●		3.50D	469	138	JS2
	500-9	6	●		3.50D	497	141	JS2
	600-9	6	●		4.00E	546	163	JS2
	450-14	4	●		3.00D	585	123	TR15
	450-14	6	●		3.00D	582	120	TR15
	500-14	6	●		3.50D	617	140	TR15
	325-16	4	●		1.85B	590	88	TR4
	350-16	4	●		1.85B	601	92	TR4
	400-16	4	●		2.15BS	622	108	TR4
	450-16	6	●		3.00D	647	123	TR4
500-16	6	●		3.00D	676	135	TR15	
DC	350-5	2	●		3.00SP	294	98	TR87S